

# Mag One by Motorola

*Introducing the BPR 40 two-way portable radio!*



## It's a little radio with a big list of features:

- 8 Channels for complete communication to a wide group
- 2 Programmable buttons for easy use and versatility
- High/Low power provides flexibility for a variety of situations
- Complete assortment of accessories increases radio versatility
- Backed by Motorola service and a one-year limited warranty\*
- Small size and light weight make it ideal for any customer
- 12 programmable features to choose from
- Attractive price that everyone can afford



\* 6 month limited warranty on accessories

**Motorola, Inc.** 1309 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A.  
www.motorola.com 1-800-927-2744

MOTOROLA and the Mag One™ by Motorola logo are registered in the U.S. Patent and Trademark Office.  
All other product or service names are the property of their respective owners. © Motorola, Inc. 2005  
12-08-2005

RD-BPR40SELLSHEET

# BPR™ 40 Portable Two-Way Radio Specifications

GENERAL SPECIFICATIONS	VHF 150-174 MHz	UHF 450-470 MHz
Channel Capacity	8	8
Model Numbers	AAH84KDS8AA1_N	AAH84RCS8AA1_N
FCC Designation	AZ489FT3810	AZ489FT4873
FCC Emissions Designators	11K0F3E/16K0F3E	11K0F3E/16K0F3E
Power Supply	One rechargeable nickel-metal hydride	
Dimensions (H x W x L)	4.21" x 2.28" x 1.46" (107 x 58 x 37 mm)	
Weight (with standard battery)	12.3 ounces (350 g)	
<b>Average Battery Life @ 5-5-90 Duty Cycle<sup>1</sup></b>		
High Power (5W/4W)	Up to 8 hours	
Low Power (1W)	Up to 11 hours	

TRANSMITTER	VHF	UHF
Frequency Range	150-174 MHz	450-470 MHz
Channel Spacing	12.5/25 kHz	12.5/25 kHz
RF Output	1 to 5W	1 to 4W
Frequency Stability <sup>2</sup>	±2.5 ppm	±2.5 ppm
Spurs and Harmonics	-63 dBc (-26 Bm)	-63 dBc (-27 Bm)
Frequency Stability <sup>2</sup>	±2.5 ppm	±2.5 ppm
FM Hum & Noise Ratio <sup>2</sup> (12.5/25 kHz)	40 dB	40 dB
Modulation Limiting <sup>2</sup> (12.5/25 kHz)	±2.5 kHz / ±5 kHz	±2.5 kHz / ±5 kHz
Audio Response (0.3-3 kHz) <sup>2</sup>	+1 to -3 dB	+1 to -3 dB
Audio Distortion <sup>2</sup>	5%	5%

RECEIVER	VHF	UHF
Frequency Range	150-174 MHz	450-470 MHz
Channel Spacing	12.5/25 kHz	12.5/25 kHz
Sensitivity <sup>2</sup> (12 dB SINAD)	<-119 dBm (.25uV)	-117.5 dBm (.3uV)
Adjacent Channel Selectivity <sup>2</sup> (12.5/25 kHz)	-60 dB / -65 dB	-60 dB / -65 dB
Intermodulation <sup>2</sup> (12.5/25 kHz)	-60 dB / -65 dB	-60 dB / -65 dB
Spurious Rejection <sup>2</sup>	65 dB	65 dB
Audio Distortion <sup>2</sup>	<5%	<5%
Hum & Noise Ratio <sup>2</sup> (12.5/25 kHz)	40 dB	40 dB
Conducted Emission	-57 dBm	-57 dBm
Audio Output @ <5% Distortion <sup>2</sup>	500 mW (at 8 ohm)	500 mW (at 8 ohm)

MILITARY STANDARDS 810 C, D, E and F								
	810 C		810 D		810 E		810 F	
	Methods	Procedures	Methods	Procedures	Methods	Procedures	Methods	Procedures
High Temperature	501.1	1	501.2	1	501.3	1	501.4	1
Low Temperature	502.1	1	502.2	1, 2	502.3	1, 2	502.4	1, 2
Temperature Shock	503.1	1	503.2	1	503.3	1	503.4	1
Solar Radiation	505.1	1	505.2	1	505.3	1	505.4	1
Humidity	507.1	2	507.2	2, 3	507.3	2, 3	507.4	3
Salt Fog	509.1	1	509.2	1	509.3	1	509.4	1
Dust	510.1	1	510.2	1	510.3	1	510.4	1
Vibration	514.2	8, 10	514.3	1	514.4	1	514.5	1

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-30°C to +60°C (Radio Only)
Sealing	Passes rain testing per IPX4
Shock & Vibration	Die-cast with impact resistance polycarbonate housing, passes EIA 603B
Dust & Humidity	Weather-resistant housing passes EIA 603B

<sup>1</sup> 5% receive, 5% transmit, 90% standby.

<sup>2</sup> All electrical specifications and methods refer to EIA/TIA 603 standards. Specifications shown are typical and subject to change without notice.